


NEVER ATTACH FLASHING TO BOTH THE CHIMNEY AND THE ROOF. THE BASE FLASHING IS ATTACHED TO THE ROOF ONLY, THE CAP FLASHING TO THE CHIMNEY ONLY. THIS ALLOWS THE HOUSE TO MOVE INDEPENDENTLY OF THE CHIMNEY

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWINGS
3. CONTRACTORS NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT WWW.MTIDRY.COM

WOOD FRAMED CHIMNEY WITH THIN STONE VENEER TO ROOF TERMINATION DETAIL



SURE CAVITY™ (SC 5016 or SC 5032) or 10MM SURE CAVITY™ (SCMM 2516 or SCMM 2532) or GRAVITY CAVITY™ (GC 1816 or GC 1832) and L&R WEEP SCREED™ (LR 3501)